



Specification

俐光機械 LKC 20G

TABLE	Table size	工作台尺寸	400×145mm
	T slot (amount×width×distance)	T型槽尺寸	3×12mm×40mm
	Max. load	工作台最大承載重量	20Kg
TRAVEL	X travel	X軸行程	240mm
	Y travel	Y軸行程	140mm
	Z travel	Z軸行程	180mm
	Spindle nose to table	Z軸主軸端面至工作台距離	60-240mm
	Spindle center to column	Z軸主軸至Z軸立柱距離	200mm
SPINDLE	Spindle taper	主軸型式	ISO20
	Spindle motor	步達馬達馬力	1000W
	Spindle speed	主軸轉速	100-5000r/min
FEED	The max moving speed	最快進給率	2000mm/min
	Power of motor X/Y axis	X / Y 扭矩	1.35Nm
	Power of motor Z axis	Z 扭矩	3.1Nm
ACCURACY	Positioning accuracy	定位精度	±0.015mm
	Repeatability accuracy	重複定位精度	±0.010mm
OTHERS	Power	電壓	230V
	Weight (NW/GW)	淨重/毛重	280/340Kg
	Overall dimension	外型尺寸	1040×860×940mm
	Packing size	包裝尺寸	1170×960×1100mm

Standard attachment

標準附件

Tool box X 1
 ISO20/ER16 tool holder X 1
 Software X 1

工具箱 X 1
 ISO20/ER16 刀把 X 1
 控制軟體 (支援標準G碼) x 1